

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 34 N., R. 59 E., MDM, NEVADA

CHAINS	
81.20	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an unmarked granite stone, 18x15x10 ins., firmly set in a mound of stone. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T34N R59E S 14   S 13 S 23   S 24</p> <p style="text-align: center;">1981</p> <p>Deposit the unmarked stone alongside the aluminum post.</p> <hr/> <p>S. 87° 23' E., bet. secs. 13 and 24.</p> <p>Over mountainous land, through scattered pinon pine, light juniper and dense sagebrush; asc. over W. slope.</p>
39.20	<p>Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T34N R59E S 13 ¼ ——— S 24</p> <p style="text-align: center;">1981</p>
80.70	<p>Secret Peak Ridge, bears NNW. and SSE.; desc. over NE. slope.</p>
89.87	<p>Point for the closing cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T34N R59E R60E CC — S 13   S 18 S 24  </p> <p style="text-align: center;">1981</p> <p>From this corner, the cor. of secs. 18 and 19, T. 34 N., R. 60 E., hereinbefore described, bears S. 0° 12' E., 10.01 chs. dist.</p> <hr/>