

69

DEPENDENT RESURVEY OF
THE FIFTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 43 EAST, MDM, NEVADA

CHAINS	<p style="text-align: center;">DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 43 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by D. H. Barker and W. W. Skinner, U. S. Deputy Surveyors, in 1875, and the Retracement Executed by W. H. Sylvester, Cadastral Surveyor, in 1959.</p> <hr/> <p>Point for the standard cor. of secs. 34 and 35, determined at record bearing and distance from the standard cor. of secs. 33 and 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R43E <u>S 34 S 35</u></p> <p style="text-align: center;">1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>WEST, along the S. bdy. of sec. 34.</p> <p>Over gently rolling land, covered with sagebrush and native grass.</p> <p>40.00 Point for the standard ¼ sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R43E <u>¼ S 34</u></p> <p style="text-align: center;">1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>80.00 The standard cor. of secs. 33 and 34, monumented with a porphyry stone, 14x7x6 ins., firmly set 7 ins. in the ground, mkd. with 3 grooves on the E. and W. faces.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
--------	--