

DEPENDENT RESURVEY OF A PORTION OF
THE EAST BOUNDARY,
T. 26 N., R. 43 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF
THE EAST BOUNDARY,
T. 26 N., R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
D. H. Barker and W. W. Skinner,
U. S. Deputy Surveyors,
in 1875.

From the sec. cor. of secs. 13, 18, 19 and 24,
monumented with a porphyry stone, 17x8x7 ins., firmly
set 10 ins. in the ground, mkd. with 3 grooves on the N.
and S. faces. Hereafter, this cor. will refer to secs.
13 and 24 only.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T26N
R43E|R44E
S 13|
S 24|

1980

Deposit the original cornerstone alongside the iron post
and raise a mound of stone, 3 ft. base, 2 ft. high, W.
of cor.

N. 0° 15' E., along the E. bdy. of sec. 13.

Over gently rolling land, covered with sagebrush and
native grass.

16.00 Wash, 10 lks. wide, 1 ft. deep, drains WSW.

40.24 Point for the ¼ sec. cor. of secs. 13 and 18, at
proportionate distance; there is no remaining evidence
of the original corner. Hereafter, this cor. will refer
to sec. 13 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T26N
R43E|R44E
¼|
S 13|

1980

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of
cor.

67.70 Wash, 25 lks. wide, 1½ ft. deep, drains NW.

72.30 Trail road, bears NW. and SE.