DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 26 N., R. 43 E., MDM, NEVADA

T. 26 N., R. 43 E., MDM, NEVADA			
	CHAINS	T26N	
-		R42E R43E	
		$\frac{S}{S} \frac{1}{12} S \qquad 7$	
		1959 1980	
	40.32	The cor. of secs. 6 and 7, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 26 N., R. 42 E., executed under Group No. 379. Remark the brass cap to read as follows:	
		T26N	
		R42E R43E	
		$S 1 \begin{vmatrix} S & 6 \\ \overline{S} & 7 \end{vmatrix}$	
		1959 1980	
-		N. 0° 04' W., along the W. bdy. of sec. 6.	
		Over gently rolling land, covered with sagebrush and bunchgrass.	
-	21.80	Trail road, bears E. and W.	
	26.70	Improved dirt road, bears NNE. and SSW.	
-	35.00	Wash, 10 1ks. wide, 2 ft. deep, drains E.	
	35.50	Wash, 10 1ks. wide, 2 ft. deep, drains SE.	
	37.06	The E ½ sec. cor. of sec. 1, T. 26 N., R. 42 E., monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 26 N., R. 42 E., executed under Group No. 379. Remark the brass cap to read as follows:	
		T26N	
		R42E R43E	
		S 1	
		1959 1980	
	40.29	The W $\frac{1}{4}$ sec. cor. of sec. 6, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 26 N., R. 42 E., executed under Group No. 379. Remark the brass cap to read as follows:	
	-		
	·		