

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 26 N., R. 43 E., MDM, NEVADA

CHAINS	
80.71	<p style="text-align: center;">T26N R43E $\frac{1}{4}$ S 2 S 1 1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 27 N., R. 43 E., resurveyed concurrently under this same group.</p>
16.20	<p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ} 35'$ E., along the E. bdy. of sec. 34.</p> <p>Over gently rolling land, covered with sagebrush and native grass.</p>
17.40	<p>Underground pipeline, bears S. $86\frac{1}{4}^{\circ}$ W. and N. $86\frac{1}{4}^{\circ}$ E.</p>
25.60	<p>Wash, 15 lks. wide, 3 ft. deep, drains W.</p>
40.25	<p>Trail road, bears ESE. and WNW.</p>
80.50	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Hereafter, this cor. will refer to sec. 34 only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R43E $\frac{1}{4}$ S 34 1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 26, 27, 34 and 35, determined latitudinally at proportionate distance, and longitudinally at record distance from the cor. of secs. 27, 28, 33 and 34; there is no remaining evidence of the original corner. Hereafter, this cor. will refer to secs. 27 and 34 only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>