

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 26 N., R. 43 E., MDM, NEVADA

CHAINS	
27.50	Improved gravel road, parallels telephone line.
36.90	Fence, bears E. and W.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T26N R43E $\frac{1}{4}$ S 3 S 2
	1980
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
64.20	Fence, bears N. $79^{\circ} 45'$ W. and S. $79^{\circ} 45'$ E.
80.58	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 27 N., R. 43 E., resurveyed concurrently under this same group.
	From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp.
	N. $0^{\circ} 17'$ E., bet. secs. 33 and 34.
	Over nearly level land, covered with sagebrush and native grass.
40.43	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T26N R43E $\frac{1}{4}$ S 33 S 34
	1980
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
56.60	Creek, 10 lks. wide, 1 ft. deep, course W.
80.86	The cor. of secs. 27, 28, 33 and 34, monumented with a granite stone, 11x10x7 ins., firmly set 6 ins. in the ground, mkd. with 3 grooves on the E. face and 1 groove on the S. face, with an aluminum cap on a $\frac{5}{8}$ in. rebar, 2 ft. long, with cap mkd. ROBERT N CALDWELL RLS 4233, firmly set alongside.