

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 26 N., R. 43 E., MDM, NEVADA

CHAINS	
	<p>T26N R43E $\frac{1}{4}$ S 5$\frac{1}{2}$S 4 1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>75.40 Telephone line, bears N. 75 3/4° W. and S. 75 3/4° E.</p> <p>76.10 Improved gravel road, parallels telephone line.</p> <p>76.70 Powerline, parallels telephone line.</p> <p>80.84 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the ground, mkd. as described in the field notes of the dependent resurvey of T. 27 N., R. 43 E., resurveyed concurrently under this same group.</p> <hr/> <p>From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 02' W., bet. secs. 31 and 32.</p> <p>Over nearly level land, covered with sagebrush and native grass.</p> <p>40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance which is in a fence, bearing E. and W. 0.70 chs. dist. to corner of fences, fences bear N., E. and S., there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p>T26N R43E $\frac{1}{4}$ S 31$\frac{1}{2}$S 32 1980</p> <p>Along fence</p> <p>80.12 The cor. of secs. 29, 30, 31 and 32, determined at the corner of fences, bearing N., S. and E. This point is locally recognized as the cor. and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>