

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 25 N., R. 43 E., MDM, NEVADA

| CHAINS |  |  |
|--------|--|--|
| 40.57  | <p>N. 1° 43' E., along the E. bdy. of sec. 5.</p> <p>Over nearly level land, covered with sagebrush and native grass.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R43E<br/><math>\frac{1}{4}</math><br/>S 5 S 4<br/><br/>1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>  |  |
| 65.85  | <p>Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R43E<br/>S 33<br/><u>S 5 S 4</u><br/>C C<br/>T25N R43E<br/><br/>1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>From this corner, the standard <math>\frac{1}{4}</math> sec. cor. of sec. 33, T. 26 N., R. 43 E., monumented with an iron post, 2<math>\frac{1}{2}</math> ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North, resurveyed concurrently under this same group, bears S. 89° 49' E., 7.41 chs. dist.</p> <p>From this same corner, the standard cor. of secs. 32 and 33, T. 26 N., R. 43 E., monumented with an iron post, 2<math>\frac{1}{2}</math> ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North, resurveyed concurrently under this same group, bears N. 89° 49' W., 32.94 chs. dist.</p> |  |