## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 25 N., R. 43 E., MDM, NEVADA

T. 25 N., R. 43 E., MDM, NEVADA	
CHAINS	N. 89° 33' W., bet. secs. 7 and 18.
	Over nearly level land, covered with sagebrush and native grass.
39.78	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T25N R43E  1 S 7  4 S 18
	1980
61.10	Fence, parallels highway.
64.80	Nevada State Highway No. 8-A, bears N. 34 3/4° E. and S. 34 3/4° W.
76.85	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a standard size aluminum private surveyor's cap on a 5/8 in. rebar, buried 18 ins. below the surface of a gravel road, bearing E. and W., with no marks legible on the aluminum cap, this point is accepted as a careful and faithful perpetuation of the position of the original corner.
	From this corner, an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above the ground, set for a reference monument as described in the field notes of T. 25 N., R. 42 E., executed under Group No. 382, bears N. 45° W., 40 ft. dist., the brass cap is missing from the iron post. There is no remaining evidence of the other reference monument.
	From this same corner, a nail firmly set in a power pole, 6 ins. above the ground, bears N. 7° 34' W., 51 lks. dist.
	From this same corner, a power pole bears S. 7° 36' W., 60 lks. dist.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 1° 10' E., bet. secs. 7 and 8.
	Over nearly level land, covered with sagebrush and native grass.
40.18	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.