DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

T. 25 N., R. 43 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T25N R43E \$\frac{1}{4}\$
S 6|S 5

1980

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

66.89

The closing cor. of secs. 5 and 6, monumented with a porphyry stone, 14x8x6 ins., firmly set 4 ins. in the ground, mkd. with 1 groove on the W. face, 5 grooves on the E. face and 6 grooves on the S. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T26N R43E S 32 S 6|S 5 C|C T25N R43E

1980

Deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 26 N., R. 43 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North, resurveyed concurrently under this same group, bears S. 89° 51' E., 4.64 chs. dist.

From this same corner, the standard cor. of secs. 31 and 32, T. 26 N., R. 43 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North, resurveyed concurrently under this same group, bears N. 89° 51' W., 35.72 chs. dist.

The point for the N $\frac{1}{4}$ sec. cor. of sec. 5 is at midpoint bet. the closing cors. and on the S. bdy. of sec. 32, T. 26 N., R. 43 E.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.