

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 27 N., R. 43 E., MDM, NEVADA

CHAINS

- 77.00 Improved dirt road, bears NNE. and S.
- 81.54 The cor. of Tps. 26 and 27 N., Rs. 42 and 43 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and showing 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west bdy. of T. 26 N., R. 43 E., executed under Group No. 379.

DEPENDENT RESURVEY OF A PORTION OF
THE WEST BOUNDARY,
T. 27 N., R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
D. H. Barker and W. W. Skinner,
U. S. Deputy Surveyors,
in 1875 and 1876.

From the cor. of Tps. 26 and 27 N., Rs. 42 and 43 E.
N. $1^{\circ} 22'$ E., along the W. bdy. of sec. 31.

Over nearly level land, covered with sagebrush and native grass.

- 13.10 Improved dirt road, bears NNW. and SSE.
- 41.33 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T27N
R42E | R43E
| $\frac{1}{4}$
| S 31

1980

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

- 56.60 Improved dirt road, bears E. and W.
- 57.00 Fence corner, from which fences bear ESE., WNW. and N., along fence.
- 82.66 The cor. of secs. 25, 30, 31 and 36, monumented with a granite stone, 18x12x10 ins., firmly set 6 ins. in the ground, mkd. with 5 grooves on the N. face and 1 groove on the S. face, located in a fence cor., from which fences bear S. and ESE. Hereafter, this cor. will refer to secs. 30 and 31 only.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.