

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 39 N., R. 52½ E., MDM, NEVADA

CHAINS	
7.60	Creek, 25 lks. wide, 1 ft. deep, course WSW.; asc. 320 ft. over S. slope.
32.00	Spur, slopes SW.; desc. 80 ft. over NW. slope.
40.03	The ¼ sec. cor. of secs. 1 and 6, monumented with a limestone, 15x10x3 ins., plainly mkd. ¼ on the W. face, firmly set and exposed 6 ins. above the ground.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T39N R52½E R53E ¼ S 1 S 6 1980</p>
	Bury the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.
	<hr/> <p>N. 0° 21' E., beginning new measurement.</p>
	Over mountainous land; asc. 90 ft. over S. slope.
18.50	Ridge, bears E. and W.; desc. 280 ft. over N. slope.
39.76	The closing cor. of Tps. 39 and 40 N., R. 53 E., hereinafter described.
	Descend 200 ft. over N. slope.
48.70	Draw, 20 lks. wide, 1 ft. deep, drains W.; asc. 520 ft. over S. slope.
74.40	The cor. of Tps. 39 and 40 N., R. 52 E., monumented with a slate stone, 16x8x6 ins., plainly mkd. with 6 notches on the N., S. and W. edges, loosely set in a mound of earth. This cor. will now refer to the cor. of Tps. 39 and 40 N., Rs. 52 and 52½ E. only.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p>T40N R52E R53E S 36 S 1 S 31 T39N S1 R52½E</p>
	<p>1979</p>