

TOWNSHIP 40 NORTH, RANGE 52 EAST, MDM, NEVADA

CHAINS

The geographic position for the southeast corner of the township is at latitude $41^{\circ} 18' 45.2''$ N., and longitude $116^{\circ} 03' 54.3''$ W., as calculated from a tie made under Group No. 585 to U.S.C. & G.S. triangulation station "WHEELER" located in section 5, T. 39 N., R. 53 E.

The mean magnetic declination was found to be $17\frac{1}{2}^{\circ}$ E.

DEPENDENT RESURVEY OF THE
EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 52 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
A. J. Hatch and J. H. Eaton,
U. S. Deputy Surveyors, in 1871,
and the Resurvey by F. Bell,
U. S. Deputy Surveyor, in 1882.

The standard cor. of secs. 35 and 36, T. 41 N., R. 52 E., monumented with a quartzite stone, 14x8x8 ins., mkd. with 1 groove on the E. face, 5 grooves on the W. face and SC on the N. face, firmly set in a mound of stone. (Record wood post.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

S C
T41N R52E
S 35|S 36

1979

Bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

N. $89^{\circ} 52'$ W., on the S. bdy. of sec. 35.

Over nearly level land, through sagebrush and native grass.

40.15 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 41 N., R. 52 E., at proportionate distance; there is no remaining evidence of the original corner.

CORNER NOT MONUMENTED