

DEPENDENT RESURVEY OF THE
EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 52 E., MDM, NEVADA

CHAINS
70.05

The closing cor. of secs. 5 and 6, hereinafter described.

80.34

Point for the standard cor. of secs. 31 and 32, T. 41 N., R. 52 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

S C
T41N R52E
S 31 | S 32

1979

Set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

N. $89^{\circ} 39'$ W., on the S. bdy. of sec. 31.

Over nearly level hay meadow.

29.16

The N $\frac{1}{4}$ sec. cor. of sec. 6, hereinafter described.

33.50

South Fork Owyhee River, 100 lks. wide, 2 ft. deep, couse NNW.; enter sagebrush.

40.17

The standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 41 N., R. 52 E., monumented with a mound of stone, no marked stone or wooden post found. This position correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

S C
T41N R52E
 $\frac{1}{4}$ S 31

1979

Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor. and set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

S. $89^{\circ} 34'$ W., beginning new measurement.

Over gently rolling land, through sagebrush.