DEPENDENT RESURVEY OF THE EIGTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF R. 52 E., MDM, NEVADA

THROUGH A FURITOR OF R. 32 E., FIDH, NEVADA	
CHAINS 1.00	Trail road, bears NW. and S.; asc. 180 ft. over an E. slope.
20.00	Spur, slopes NE.; desc. 40 ft. over a W. slope.
27.40	The closing cor. of T. 40 N., Rs. 51 and 52 E., hereinafter described.
•	Desc. 60 ft. over a W. slope.
32.00	Draw, drains NE.; asc. 100 ft. over an E. slope.
40.26	The standard corner of T. 41 N., Rs. 51 and 52 E., monumented with a mound of stone. No marked stone or wooden post found. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.
	At the corner point
·	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

S C T41N R51E|R52E S 36|S 31

-1979

Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor. and set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 40 N., R. 52 E., MDM, NEVADA

Reestablishment of the Survey Executed by
A. J. Hatch and J. H. Eaton,
U. S. Deputy Surveyors, in 1871, and
the Resurvey by T. H. Lowe,
U. S. Deputy Surveyor, in 1900.

The cor. of T. 39 N., R. $52\frac{1}{2}$ E. and Tps. 39 and 40 N., R. 52 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 39 N., R. $52\frac{1}{2}$ E., executed concurrently under this same group.