

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 40 N., R. 52 E., MDM, NEVADA

CHAINS	
	N. 3° 20' E., along the E. bdy. of sec. 36.
	Over mountainous land, through sagebrush; desc. 520 ft. over a NE. slope.
21.00	Draw, drains NW.
24.00	Draw, drains W.; asc. 400 ft. over a S. slope.
39.05	The E $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a granite stone, 16x12x10 ins., plainly mkd. $\frac{1}{4}$ on the W. face and loosely set in a small mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T40N R52E R53E <math>\frac{1}{4}</math> S 36 </p>
	1979
	Bury the original cornerstone and set a steel fence post, 5 $\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.
	<hr style="width: 25%; margin: auto;"/> <p>N. 0° 12' W., beginning new measurement.</p>
	Over mountainous land; asc. 160 ft. over a S. slope.
8.30	Ridge, bears E. and W.; desc. N. slope, changing to NW.
9.94	The closing corner of secs. 30 and 31, T. 40 N., R. 53 E., monumented with a granite stone, 14x8x8 ins., plainly mkd. with 1 notch on the S. edge, 5 notches on the N. edge and CC on the E. face, loosely set in a mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, 2 $\frac{1}{2}$ ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T40N R52E R53E S 36  <math>\frac{S}{S}</math> <math>\frac{30}{31}</math> CC</p>
	1979