

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 40 N., R. 52 E., MDM, NEVADA

CHAINS
79.18

The cor. of secs. 24 and 25, monumented with a quartzite stone, 12x10x4 ins., plainly mkd. with 2 grooves on the S. face and 4 grooves on the N. face, firmly set in a mound of stone, with a steel fence post firmly set alongside.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N
R52E R53E
S 24 | S 19
S 25 |

1979

Bury the original cornerstone and reset the steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 40 N., R. 52 E., MDM, NEVADA

Reestablishment of the Survey Executed by
A. J. Hatch and J. H. Eaton, U. S. Deputy Surveyors,
in 1871.

From the cor. of T. 39 N., R. 52½ E. and Tps. 39 and 40 N., R. 52 E.

N. 89° 30' W., bet. secs. 1 and 36.

Over mountainous land, through sagebrush; desc. 500 ft. over a W. slope.

40.02

The ¼ sec. cor. of secs. 1 and 36, monumented with a basalt stone, 14x6x5 ins., plainly mkd. ¼ on the N. face, firmly set flush with the surface of the ground.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, 2 ft. base to top, with brass cap mkd.

T40N R52E
¼ S 36
S 1

T39N

1979

Bury the original cornerstone and set a steel fence post, 5½ ft. long, 20 ins. in the ground, alongside the iron post.