

246

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 40 N., R. 52 E., MDM, NEVADA

CHAINS  
79.76

Point for the cor. of secs. 10, 11, 14 and 15,  
determined latitudinally at proportionate distance and  
longitudinally in a fence, bearing N. and S.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T40N R52E  
S 10 | S 11  
S 15 | S 14

1979

From this corner, point for the closing corner of secs.  
2 and 3, bears N.  $0^{\circ} 11' W.$ , 159.12 chs. dist., at  
proportionate distance and on the Eighth Standard  
Parallel North; there is no remaining evidence of the  
original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T41N R52E  
S 35  
S 3 | S 2

T40N  
C C

1979

Set a steel fence post,  $5\frac{1}{2}$  ft. long, 22 ins. in the  
ground, alongside the iron post. From this corner, the  
standard corner of secs. 34 and 35, T. 41 N., R. 52 E.,  
bears N.  $89^{\circ} 52' W.$ , 9.85 chs. dist.

This control line was fully retraced and careful search  
was made for evidence of intervening corners, none of  
which were recovered.

From the cor. of secs. 11, 12, 13 and 14.

N.  $89^{\circ} 00' W.$ , bet. secs. 11 and 14.

Over nearly level land, through sagebrush, along fence.

20.10 Fence corner, from which fences bear N., E. and WSW.

40.01 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14, at  
proportionate distance; there is no remaining evidence  
of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T40N R52E  
S 11  
 $\frac{1}{4}$  S 14

1979