DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 40 N., R. 52 E., MDM, NEVADA

CHAINS 4.00

South Fork Owyhee River, 75 lks. wide, 2 ft. deep, course NW.

40.10

Point for the ½ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N R52E \$ 6|S 5

1979

Set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

80.00

Intersect the Eighth Standard Parallel North.

Point for the closing corner of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. flush with the surface of the ground, with brass cap mkd.

1979

Set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

From this corner, the standard cor. of secs. 31 and 32, T. 41 N., R. 52 E., bears N. 89 $^{\circ}$ 39 $^{\circ}$ W., 10.29 chs. dist.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 6 is at proportionate distance and on the S. bdy. of sec. 31, T. 41 N., R. 52 E.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R52E

1 S 6 T40N R52E

1979

Set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 41 N., R. 52 E., bears N. 89° 39' W., 11.01 chs. dist.