

336

DEPENDENT RESURVEY OF THE
EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 66 E., MDM, NEVADA

<p>CHAINS</p> <p>80.48</p>	<p>The original standard cor. of secs. 31 and 32, monumented with a wooden post, 12 ins. long, 1 in. square, with illegible scribe marks visible, firmly set alongside a steel fence post.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">S C T41N R66E <u>S 31 S 32</u></p> <p style="text-align: center;">1980</p> <p>Reset the wooden post and steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.</p> <hr/> <p>N. 88° 36' W., along the S. bdy. of sec. 31.</p> <p>Over rolling land, through scattered sagebrush.</p> <p>20.32 The N ¼ sec. cor. of sec. 5, T. 40 N., R. 66 E., hereinafter described.</p> <p>40.46 Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">S C T41N R66E <u>¼ S 31</u></p> <p style="text-align: center;">1980</p> <p>Set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.</p> <p>65.02 The closing cor. of secs. 5 and 6, T. 40 N., R. 66 E., hereinafter described.</p> <p>80.92 The original standard cor. of T. 41 N., Rs. 65 and 66 E., monumented with the decayed remains of a wooden post, in pieces, with illegible scribe marks visible, alongside a steel fence post.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>	
----------------------------	---	--