

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 40 N., R. 66 E., MDM, NEVADA

CHAINS	
	T40N R66E S 31 S 32 S 6 S 5 T39N 1980 Reset the wooden post and steel fence post alongside the aluminum post. From this cor., U.S.G.S. Bench Mark, monumented with a standard brass tablet set in concrete, with cap mkd. 5656 GWM 46 1939, bears S. 86° 43' W., 30.02 chs. dist. N. 89° 57' W., bet. secs. 6 and 31. Over nearly level land, through scattered sagebrush. 7.50 Trail road, bears N. and S. 22.00 Toano Wash, 20 lks. wide, 6 ft. deep, drains NNW. 37.52 The original $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a shaved wooden post, 24 ins. long, 2 ins. diam., with illegible scribe marks visible, firmly set alongside a steel fence post. At the corner point Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T40N R66E $\frac{1}{4}$ S 31 S 6 T39N 1980 Reset the wooden post and steel fence post alongside the aluminum post. S. 89° 40' W., beginning new measurement. Over nearly level land. 13.46 The original closing cor. of Tps. 39 and 40 N., R. 66 E., monumented with a wooden post, 24 ins. long, 2 ins. square, with illegible scribe marks visible, firmly set alongside a steel fence post. At the corner point