

388

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 66 E., MDM, NEVADA

CHAINS

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} \text{T40N R66E} \\ \text{S 30} \\ \hline \frac{1}{4} \text{ S 31} \end{array}$$

1980

Reset the wooden post and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.

S.  $45^{\circ} 01'$  W., beginning new measurement.

Over rolling land.

12.87 Point for the closing cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} \text{T40N} \\ \text{T40N | R66E} \\ \text{S 25 | } \frac{\text{S 30}}{\text{S 31}} \text{ CC} \\ \text{R65E |} \end{array}$$

1980

Set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.

From this corner, the cor. of secs. 25 and 36, T. 40 N., R. 65 E., bears S.  $1^{\circ} 55'$  W., 11.78 chs. dist.

The point for the  $W \frac{1}{4}$  sec. cor. of sec. 31 is at midpoint and on the E. bdy of sec. 36, T. 40 N., R. 65 E.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} \text{T40N} \\ \text{R65E R66E} \\ \text{ } \frac{1}{4} \\ \text{ } | \text{S 31} \end{array}$$

1980

Set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.

From this corner, the  $E \frac{1}{4}$  sec. cor. of sec. 36, T. 40 N., R. 65 E., bears S.  $1^{\circ} 20'$  W., 16.27 chs. dist.