

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 66 E., MDM, NEVADA

## CHAINS

N.  $89^{\circ} 44'$  W., bet. secs. 18 and 19.

Over rolling land, through scattered sagebrush.

40.46

The original  $\frac{1}{4}$  sec. cor. of secs. 18 and 19, monumented with a shaved wooden post, 30 ins. long, 3 ins. diam., with illegible scribe marks visible, firmly set 10 ins. in the ground.

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{T40N R66E} \\ \frac{1}{4} \frac{\text{S 18}}{\text{S 19}} \end{array}$$

1980

Reset the wooden post and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.

S.  $89^{\circ} 42'$  W., beginning new measurement.

Over rolling land.

5.15

The original closing cor. of secs. 18 and 19, monumented with a wooden post, 30 ins. long, 2 ins. square, with illegible scribe marks visible, firmly set 15 ins. in the ground.

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{T40N} \\ \text{T40N|R66E} \\ \text{S 13|} \frac{\text{S 18}}{\text{S 19}} \text{CC} \\ \text{R65E|} \end{array}$$

1980

Reset the wooden post and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.

From this corner, the cor. of secs. 13 and 24, T. 40 N., R. 65 E., bears S.  $1^{\circ} 29'$  W., 20.66 chs. dist.

The point for the W  $\frac{1}{4}$  sec. cor. of sec. 19 is at midpoint and on the E. bdy. of sec. 24, T. 40 N., R. 65 E.