

415

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 40 N., R. 65 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 40 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
A. J. Hatch and J. H. Easton, U. S. Deputy Surveyors,
in 1870, and the Resurvey Executed by
H. Fitzhugh, U. S. Deputy Surveyor,
in 1894.

From the SE. cor. of sec. 36, T. 40 N., R. 65 E.,
monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly
set and exposed 6 ins. above the ground, with aluminum
cap mkd. as described in the field notes of the
dependent resurvey of T. 40 N., R. 66 E., executed
concurrently under this same group.

N. $88^{\circ} 43'$ W., along the S. bdy. of sec. 36.

Over nearly level land, covered with medium sagebrush
and scattered native grass.

32.24 The closing cor. of Tps. 39 N., Rs. 65 and 66 E.,
hereinafter described.

39.94 Point for the S $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate
distance; there is no remaining evidence of the original
corner.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T40N R65E

$\frac{1}{4}$ S 36

T39N R65E

1980

Set a steel fence post, $5\frac{1}{2}$ ft. long, 2 ft. in the
ground, alongside the aluminum post.

79.88 The cor. of secs. 35 and 36, monumented with the decayed
remains of a wooden post, 16 ins. long, 3 ins. square,
with illegible scribe marks visible, wired to a steel
rebar, $\frac{5}{8}$ ins. diam., 18 ins. long, firmly set 12 ins.
in the ground, with steel fence post, 5 ft. long, firmly
set 2 ft. in the ground, alongside the wooden post.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.