

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 38 N., R. 52½ E., MDM, NEVADA

CHAINS							
	<div>T38N</div> <div>R52½E R53E</div> <div>¼ </div> <div>S 12 </div> <div>1980</div> <div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.</div> <div></div> <div>N. 0° 56' W., beginning new measurement.</div> <div>Over mountainous land.</div> <tr><td>33.71</td><td><div>The closing cor. of secs. 6 and 7, T. 38 N., R. 53 E., monumented with a basalt stone, 17x12x8 ins., firmly set and exposed 4 ins. above the ground, mkd. with 5 grooves on the S. face and 1 groove on the N. face, with a mound of stone E. of cor.</div><div>At the corner point</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</div><div><div>T38N</div><div>R52½E R53E</div><div>S 12 S 6</div><div> S 7CC</div></div><div>1981</div><div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</div><tr><td>35.20</td><td><div>Aluminum tower powerline, bears N. 80¼° E. and S. 80¼° W.</div></td></tr><tr><td>40.26</td><td><div>The cor. of secs. 1 and 12, monumented with a basalt stone, 15x14x6 ins., dimly mkd., firmly set and exposed 6 ins. above the ground and in a collar of stone.</div><div>At the corner point</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T38N</div><div>R52½E R53E</div><div>S 1 S 6</div><div>S 12 </div></div><div>1980</div><div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</div><div></div></td></tr></td></tr>	33.71	<div>The closing cor. of secs. 6 and 7, T. 38 N., R. 53 E., monumented with a basalt stone, 17x12x8 ins., firmly set and exposed 4 ins. above the ground, mkd. with 5 grooves on the S. face and 1 groove on the N. face, with a mound of stone E. of cor.</div> <div>At the corner point</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</div> <div><div>T38N</div><div>R52½E R53E</div><div>S 12 S 6</div><div> S 7CC</div></div> <div>1981</div> <div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</div> <tr><td>35.20</td><td><div>Aluminum tower powerline, bears N. 80¼° E. and S. 80¼° W.</div></td></tr> <tr><td>40.26</td><td><div>The cor. of secs. 1 and 12, monumented with a basalt stone, 15x14x6 ins., dimly mkd., firmly set and exposed 6 ins. above the ground and in a collar of stone.</div><div>At the corner point</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T38N</div><div>R52½E R53E</div><div>S 1 S 6</div><div>S 12 </div></div><div>1980</div><div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</div><div></div></td></tr>	35.20	<div>Aluminum tower powerline, bears N. 80¼° E. and S. 80¼° W.</div>	40.26	<div>The cor. of secs. 1 and 12, monumented with a basalt stone, 15x14x6 ins., dimly mkd., firmly set and exposed 6 ins. above the ground and in a collar of stone.</div> <div>At the corner point</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T38N</div><div>R52½E R53E</div><div>S 1 S 6</div><div>S 12 </div></div> <div>1980</div> <div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</div> <div></div>
33.71	<div>The closing cor. of secs. 6 and 7, T. 38 N., R. 53 E., monumented with a basalt stone, 17x12x8 ins., firmly set and exposed 4 ins. above the ground, mkd. with 5 grooves on the S. face and 1 groove on the N. face, with a mound of stone E. of cor.</div> <div>At the corner point</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</div> <div><div>T38N</div><div>R52½E R53E</div><div>S 12 S 6</div><div> S 7CC</div></div> <div>1981</div> <div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</div> <tr><td>35.20</td><td><div>Aluminum tower powerline, bears N. 80¼° E. and S. 80¼° W.</div></td></tr> <tr><td>40.26</td><td><div>The cor. of secs. 1 and 12, monumented with a basalt stone, 15x14x6 ins., dimly mkd., firmly set and exposed 6 ins. above the ground and in a collar of stone.</div><div>At the corner point</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T38N</div><div>R52½E R53E</div><div>S 1 S 6</div><div>S 12 </div></div><div>1980</div><div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</div><div></div></td></tr>	35.20	<div>Aluminum tower powerline, bears N. 80¼° E. and S. 80¼° W.</div>	40.26	<div>The cor. of secs. 1 and 12, monumented with a basalt stone, 15x14x6 ins., dimly mkd., firmly set and exposed 6 ins. above the ground and in a collar of stone.</div> <div>At the corner point</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T38N</div><div>R52½E R53E</div><div>S 1 S 6</div><div>S 12 </div></div> <div>1980</div> <div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</div> <div></div>		
35.20	<div>Aluminum tower powerline, bears N. 80¼° E. and S. 80¼° W.</div>						
40.26	<div>The cor. of secs. 1 and 12, monumented with a basalt stone, 15x14x6 ins., dimly mkd., firmly set and exposed 6 ins. above the ground and in a collar of stone.</div> <div>At the corner point</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T38N</div><div>R52½E R53E</div><div>S 1 S 6</div><div>S 12 </div></div> <div>1980</div> <div>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</div> <div></div>						