

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 38 N., R. 52 E., MDM, NEVADA

| | |
|--------|---|
| CHAINS | <p>NORTH, beginning new measurement.</p> <p>Over rolling land.</p> <p>6.44 The W $\frac{1}{4}$ sec. cor. of sec. 12, T. 38 N., R. 52$\frac{1}{2}$ E., hereinafter described.</p> <p>38.70 Aluminum tower powerline, bears N. 80$\frac{1}{4}$° E. and S. 80$\frac{1}{4}$° W.</p> <p>40.12 The cor. of secs. 1, 6, 7 and 12, monumented with a quartz stone, 12x8x6 ins., no marks visible, firmly set in a mound of stone. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner. This corner now refers to the cor. of secs. 1 and 12 only.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T38N R52E R52$\frac{1}{2}$E $\frac{S}{S}$ $\frac{1}{12}$ S 12</p> <p>1981</p> </div> <p>Deposit the quartz stone and set a steel fence post, 5$\frac{1}{2}$ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 1° 59' W., along the E. bdy. of sec. 1.</p> <p>Over rolling land, covered with sagebrush and native grass.</p> <p>6.59 The closing cor. of secs. 1 and 12, T. 38 N., R. 52$\frac{1}{2}$ E., hereinafter described.</p> <p>40.31 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the $\frac{1}{4}$ sec. cor. of sec. 1 only.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T38N R52E R52$\frac{1}{2}$E $\frac{1}{4}$ S 1 </p> <p>1981</p> </div> <p>Set a steel fence post, 5$\frac{1}{2}$ ft. long, alongside the iron post.</p> |
|--------|---|