

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 39 N., R. 51 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R51E S 31   S 32 S 6   S 5 T38N</p> <p style="text-align: center;">1979</p>
	<p>N. 89° 56' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land, covered with sagebrush and native grass.</p>
17.00	Graded gravel road, bears WSW. and ENE.
39.96	<p>The ¼ sec. cor. of secs. 6 and 31, monumented with a basalt stone, 16x16x4 ins., plainly mkd. ¼ on the N. face, firmly set and exposed 8 ins. above the ground, with a mound of stone to the N.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R51E ¼ S 31 S 6 T38N</p> <p style="text-align: center;">1979</p>
	<p>Bury the original cornerstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>From this corner, a U.S.C. &amp; G.S. Bench Mark, monumented with a standard brass tablet, stamped "N 76 1934," firmly set in a concrete post, 12 ins. square, and exposed 5 ins. above the ground, bears S. 61° 02' E., 6.74 chs. dist.</p> <p>From this same corner, a wooden post, 2 ins. diam., 4 ft. long, wired to a firmly set steel fence post, bears S. 69° 41' E., 2.47 chs. dist.</p>
	<p>S. 89° 58' W., beginning new measurement.</p>
	Over gently rolling land, covered with sagebrush.
7.40	Spur, slopes SSE.
30.00	Wash, 20 lks. wide, 1 ft. deep, drains S.