

190

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 37 N., R. 26 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 37 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
Emil Voigt, U. S. Cadastral Engineer,
in 1920.

From the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, Tps. 36 and 37
N., R. 26 E., monumented with an iron post, 1 in. diam.,
firmly set in a mound of stone, with brass cap mkd. as
described in the field notes of the survey and
retracement of the N. bdy. of T. 36 N., R. 26 E.,
executed under Group No. 83.

Remark the brass cap to read as follows:

$$\begin{array}{r} \text{T37N R26E} \\ \text{S 35} \\ \hline \frac{1}{4} \text{S 2} \\ \text{T36N R26E} \end{array}$$

1920
1981

WEST, bet. secs. 2 and 35.

Over rolling land, covered with scattered sagebrush,
shadscale and native grass.

32.11 Intersect the E. bdy. of sec. 34, T. 37 N., R. 26 E.,
concurrently resurveyed under this same Group.

Point for the closing cor. of secs. 2 and 35, Tps. 36
and 37 N., Rs. 26 E.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

$$\begin{array}{r} | \text{T37N} \\ \text{T37N} | \text{R26E} \\ \text{S 34} | \text{S 35} \\ \text{R26E} | \text{S 2} \\ | \text{T36N} \\ | \text{R26E} \end{array} \text{CC}$$

1981

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of
cor.

From this corner, the SE. cor. of sec. 34, hereinafter
described, bears S. $1^{\circ} 30' \text{ W.}$, 11.90 chs. dist.

From this same corner, the cor. of secs. 2, 3, 34 and
35, Tps. 36 and 37 N., R. 26 E., established by Emil
Voigt in 1920, bears WEST, 7.95 chs. dist., monumented
with an iron post, 2 ins. diam., firmly set in a mound
of stone, with brass cap mkd. as described in the field
notes of the retracement of a portion of the N. bdy. of
T. 36 N., R. 26 E., executed under Group No. 83.
Hereafter, this corner will function as an amended
monument.