

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 37 N., R. 26 E., MDM, NEVADA

CHAINS	
	Set a steel fence post, 5½ ft. long, alongside the iron post.
47.77	The N. ¼ sec. cor. of sec. 4, T. 36 N., R. 26 E., hereinafter described.
54.00	Trail road, bears irregularly N. and S.
62.79	Point for the W 1/16 sec. cor. of secs. 4 and 33. Hereafter, this corner will refer to sec. 33 and Angle Point No. 1, Tract No. 37 only.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T37N R26E W 1/16 S 33 AP 1 S 4 TR37 T36N R26E </p> <p style="text-align: center;">1981</p>
	Set a steel fence post, 5½ ft. long, alongside the iron post.
75.50	Creek, 30 lks. wide, 1 ft. deep, course NNW.
83.72	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. Hereafter, this corner will refer to the sec. cor. of secs. 32 and 33, identical with Angle Points No. 2, Tract No. 37 and No. 1, Tract No. 38 only.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T37N R26E S 32 S 33 AP 1 AP 2 TR38 TR37 </p> <p style="text-align: center;">1981</p>
	Set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.
	N. 88° 59' W., along the S. bdy. of sec. 32.
	Over gently rolling land, covered with scattered saltgrass and greasewood.
4.13	The closing cor. of secs. 4 and 5, T. 36 N., R. 26 E., hereinafter described.