

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 37 N., R. 26 E., MDM, NEVADA

CHAINS

T37N R26E
S 31 | S 32
S 5
T36N R26E

1979

Deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 82° 07' W., along the S. bdy. of sec. 31.

Over nearly level land, covered with scattered greasewood.

2.98 The closing cor. of secs. 5 and 6, T. 36 N., R. 26 E., hereinafter described.

42.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. Hereafter, this corner will refer to sec. 31 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T37N R26E
 $\frac{1}{4}$ S 31

T36N R26E

1981

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

43.36 The N. $\frac{1}{4}$ sec. cor. of sec. 6, T. 36 N., R. 26 E., hereinafter described.

83.36 The cor. of Tps. 36 and 37 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 37 N., R. 25 E., executed under Group No. 31.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 36 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G. W. Garside, U. S. Deputy Surveyor,
in 1872, and Resurveyed by
Emil Voigt, U. S. Cadastral Engineer,
in 1920.