

INDEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 36 N., R. 26 E., MDM, NEVADA

CHAINS	
	<p>From this corner, the S <math>\frac{1}{4}</math> sec. cor. of sec. 34, T. 37 N., R. 26 E., bears EAST, 7.65 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 36 N., R. 26 E., executed under Group No. 83.</p> <p>N. 0° 03' E., bet. secs. 8 and 9.</p> <p>Over nearly level dry lakebed.</p>
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E <math>\frac{1}{4}</math> S. 8 S 9  1979</p>
	<p>Raise a mound of stone, 3 ft. base, 1<math>\frac{1}{2}</math> ft. high, W. of cor.</p>
68.00	<p>Wash, 50 lks. wide, 3 ft. deep, drains SW.</p>
71.80	<p>Leave dry lakebed, enter nearly level land, covered with scattered undergrowth.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S 5 S 4 <hr/>S 8 S 9  1979</p>
	<p>Raise a mound of stone, 3 ft. base, 1<math>\frac{1}{2}</math> ft. high, W. of cor.</p>
	<p>From this corner, the original cor. of secs. 4, 5, 8 and 9, bears S. 19° 01' E., 12.95 chs. dist., monumented with a basalt stone, 8x6x6 ins., firmly set in a mound of stone, plainly mkd. with 4 grooves on the E. face and dimly mkd. with 5 grooves on the S. face. Add the marks AM and bury the cornerstone 1 ft. below the surface of the ground.</p>
	<p>Land, nearly level. Soil, sandy clay. Undergrowth, greasewood.</p> <hr/>