

202

INDEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 36 N., R. 26 E., MDM, NEVADA

CHAINS

From this corner, the original $\frac{1}{4}$ sec. cor. of secs. 4 and 5, bears S. $27^{\circ} 11' E.$, 11.91 chs. dist., monumented with a granite stone, 6x4x2 ins., firmly set in a circle of stone, dimly mkd. $\frac{1}{4}$ on the W. face. Add the marks AM and bury the cornerstone 1 ft. below the surface of the ground.

49.67 Intersect line 3-4 of Tract No. 38, from which Cor. No. 4, identical with Cor. No. 3 of Tract No. 37, bears S. $89^{\circ} 37' E.$, 4.76 chs. dist., hereinafter described.

70.00 Intersect the S. bdy. of sec. 32, T. 37 N., R. 26 E.

Point for the closing cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T37N R26E
S 32
S 5 | S 4
T36N R26E
C C

1981

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the cor. of secs. 32 and 33, T. 37 N., R. 26 E., bears S. $88^{\circ} 59' E.$, 4.13 chs. dist., hereinbefore described.

Land, gently rolling.

Soil, sandy clay.

Undergrowth, greasewood, shadscale and saltgrass.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 4, is on the S. bdy. of sec. 33, T. 37 N., R. 26 E., and at midpoint bet. the closing corners.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T37N R26E
 $\frac{1}{4}$ S 4
T36N R26E

1981

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, the S $\frac{1}{4}$ sec. cor. of sec. 33, T. 37 N., R. 26 E., bears S. $88^{\circ} 59' E.$, 5.91 chs. dist., hereinbefore described.