DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 37 N., R. 26 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 37 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by G. W. Garside, U. S. Deputy Surveyor, in 1872.

From the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a basalt stone, 22x15x14 ins., plainly mkd. with 4 grooves on the face, 2 grooves on the E. face and 6 grooves on the N. and S. faces, firmly set in a mound of stone. This corner now refers to the cor. of secs. 2 and 3 only. (Record: wooden post.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T38N R26E

S 3|S 2 T37N R26E

1981

Deposit the original cornerstone and set a steel fence post,  $5\frac{1}{2}$  ft. long, alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

N. 87° 46' W., along the N. bdy. of sec. 3.

Over rolling land, covered with scattered greasewood, shadscale, and native grass.

41.65

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, monumented with a sandstone,  $18 \times 10 \times 8$  ins., plainly mkd. with  $\frac{1}{4}$  on the N. face, firmly set in a mound of stone. This corner now refers to the cor. of sec. 3 only. (Record: wooden post.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T38N R26E

14 S 3 T37N R26E

1981

Deposit the original cornerstone alongside the iron post.