

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 37 N., R. 26 E., MDM, NEVADA

CHAINS

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, head of spring, 20 lks. diam., drains W., bears S. $7^{\circ} 41'$ E., 10.12 chs. dist.

N. $88^{\circ} 13'$ W., along the N. bdy. of sec. 6.

Over gently rolling land, covered with medium greasewood and scattered shadscale and native grass.

1.70 Wash, 80 lks. wide, 12 ft. deep, drains irregularly S.

45.21 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of sec. 6 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T38N R26E

$\frac{1}{4}$ S 6
T37N R26E

1981

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

89.02 The cor. of Tps. 37 and 38 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 25 E., executed under Group No. 31.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G. W. Garside, U. S. Deputy Surveyor,
in 1877.

From the SE. cor. of sec. 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 37 N., R. 26 E., executed concurrently under this same Group.

N. $1^{\circ} 30'$ E., on the E. bdy. of sec. 34.

Over gently rolling land, covered with scattered shadscale, Brigham tea and native grass.