

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 37 N., R. 61 E., MDM, NEVADA

CHAINS

T37N T37N
S 12|R62E
S 13|S 7
R61E|

1980

Bury the original cornerstone and set a steel fence post, 5 ft. long, alongside the aluminum post.

N. 0° 24' W., bet. secs. 7 and 12.

Over rolling land, covered with scattered sagebrush.

- 8.00 Powerline, bears N. 79½° E. and S. 79½° W.
- 38.08 The ¼ sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the retracement and partial survey of the W. bdy. of T. 37 N., R. 62 E., executed under Group No. 29. Add the marks T37N R61E R62E 1980 on the brass cap.
- N. 0° 06' E., beginning new measurement.
- Over rolling land.
- 11.23 Intersect right-of-way Interstate Highway No. 80 fence, bears N. 78° 20' W. and S. 78° 20' E.
- 14.32 Eastbound lane of Interstate Highway No. 80, bears N. 78¼° W. and S. 78¼° E.
- 17.42 Westbound lane of Interstate Highway No. 80, bears N. 78¼° W. and S. 78¼° E.
- 20.51 Intersect right-of-way Interstate Highway No. 80 fence, bears N. 78° 20' W. and S. 78° 20' E.
- 29.00 Telephone line, bears N. 80° W. and S. 80° E.
- 30.60 Trail road, bears WNW. and ESE.
- 40.32 The cor. of secs. 1, 6, 7 and 12, identical with a station of the Nevada Planning Division of the Nevada State Highway Department, monumented with an iron post, 3 ins. diam., firmly set and exposed 12 ins. above the ground, with brass cap mkd. as described in the field notes of the retracement and partial resurvey of the W. bdy. of T. 37 N., R. 62 E., executed under Group No. 29, and is at latitude 41° 06' 48.365" N. and longitude 115° 01' 19.359" W.
- From this corner, U.S.C. & G.S. triangulation station "CABLE," monumented with a standard brass tablet stamped CABLE 1957, set in the top of a 10 in. square concrete monument projecting 3 ins. above the ground, bears S. 43° 23' W., 43.30 chs. dist.

N. 0° 22' W., bet. secs. 1 and 6.