

304

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 33 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE
NINTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 33 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G. W. Garside and C. S. Preble,
U. S. Deputy Surveyors, in 1874,
and the Resurvey Executed by
W. H. Sylvester, Cadastral Surveyor,
in 1958.

From the standard cor. of T. 46 N., Rs. 33 and 34 E.,
monumented with an iron post, 3 ins. diam., firmly set
showing 10 ins. above the ground, with brass cap mkd. as
described in the field notes of the dependent resurvey
of the E. bdy. of T. 46 N., R. 33 E., executed under
Group No. 110.

N. 89° 22' W., along the S. bdy. of sec. 36.

Over nearly level land, covered with medium sagebrush
and native grass.

40.18 The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with an
iron post, 1 in. diam., firmly set showing 6 ins. above
the ground, with brass cap mkd. as described in the
field notes of the dependent resurvey of the S. bdy. of
T. 46 N., R. 33 E., executed under Group No. 370.

N. 89° 00' W., beginning new measurement.

Over nearly level land.

20.09 Point for the W 1/16 sec. cor. of sec. 36.

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

W 1/16 S 36

1981

Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the
aluminum post.

33.84 The closing cor. of secs. 1 and 2, T. 45 N., R. 33 E.,
bears SOUTH, 0.05 chs. dist., monumented with an iron
post, 2 $\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the
ground, with brass cap mkd. as described in the field
notes of the dependent resurvey of the S. bdy. of T. 46
N., R. 33 E., executed under Group No. 370.