

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 33 EAST, MDM, NEVADA

CHAINS
40.18

The standard cor. of secs. 35 and 36, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 46 N., R. 33 E., executed under Group No. 370.

From this cor., the N. $\frac{1}{4}$ sec. cor. of sec. 2, T. 45 N., R. 33 E., monumented with an iron post, 1 in. diam., firmly set in concrete showing 9 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 46 N., R. 33 E., executed under Group No. 370, identical with U.S.G.S. triangulation station and benchmark QUARTER COR T45NR33E, bears N. $88^{\circ} 58'$ W., 33.77 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 46 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G. W. Garside and C. S. Preble,
U. S. Deputy Surveyors, in 1874,
and the Resurvey Executed by
W. H. Sylvester, Cadastral Surveyor,
in 1958.

From the cor. of secs. 35 and 36, on the S. bdy. of the Tp.

N. $0^{\circ} 26'$ E., bet. secs. 35 and 36.

Over nearly level land, covered with medium sagebrush, rabbitbrush and native grass.

4.60 Fence, bears E. and W.

5.80 Improved gravel road, bears E. and W.

6.20 Enter alfalfa field.

40.28 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with aluminum cap mkd.

T46N R33E

$\frac{1}{4}$

S 35|S 36

1981

60.42 Point for the N $1/16$ sec. cor. of secs. 35 and 36.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with aluminum cap mkd.