

308

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 46 N., R. 33 E., MDM, NEVADA

CHAINS
20.27

Point for the W 1/16 sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 24}{S\ 25}$

1981

Set a steel fence post, 5½ ft. long, alongside the aluminum post.

From this cor., cor. of fences bear N. 12 lks. dist., from which fences bear N. and W.

Along fence.

40.54

The cor. of secs. 23, 24, 25 and 26.

SUBDIVISION OF SECTION 25
T. 46 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

From the ¼ sec. cor. of secs. 25 and 36.

N. 0° 32' E., on the N. and S. centerline of sec. 25.

Over gently rolling hills, covered with medium sagebrush.

20.16

Point for the C-S 1/16 sec. cor. of sec. 25.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C
S 1/16 | S 25
C

1981

Set a steel fence post, 5½ ft. long, alongside the aluminum post.

40.32

Point for the center ¼ sec. cor. of sec. 25, at intersection with the E. and W. centerline.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T46N R33E

C¼ S 25

1981

Set a steel fence post, 5½ ft. long, alongside the aluminum post.