

SUBDIVISION OF SECTION 36  
T. 46 N., R. 33 E., MDM, NEVADA

## CHAINS

T46N R33E

C $\frac{1}{4}$  S 36

1981

Set a steel fence post, 5 $\frac{1}{2}$  ft. long, alongside the aluminum post.

60.62 Point for the C-N 1/16 sec. cor. of sec. 36.

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C  
N 1/16 | S 36  
C

1981

Set a steel fence post, 5 $\frac{1}{2}$  ft. long, alongside the aluminum post.

76.20 Powerline, bears N. 41° W. and S. 41° E.

76.30 Fence, parallels powerline.

80.79 The  $\frac{1}{4}$  sec. cor. of secs. 25 and 36.

From the E  $\frac{1}{4}$  sec. cor. of sec. 36, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set showing 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of the Tp., executed under Group No. 110. Remark the brass cap to read as follows:

T46N  
R33E R34E  
 $\frac{1}{4}$  |  
S 36 |

1981

1923

N. 89° 14' W., on the E. and W. centerline of sec. 36.

Over nearly level land, through a field.

8.50 Fence, parallels powerline.

8.52 Powerline, bears N. 41° W. and S. 41° E.

40.24 The center  $\frac{1}{4}$  sec. cor. of sec. 36.

60.36 Point for the C-W 1/16 sec. cor. of sec. 36.

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.