## DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 19 EAST, MDM, NEVADA

 	THROUGH A PORTION OF RANGE 19 EAST, MDM, NEVADA
CHAINS	Deposit the original cornerstone alongside the aluminum post.
	S. 89° 49' W., along the S. bdy. of sec. 32.
	Over mountainous land, covered with medium sagebrush, native grass, scattered Brigham tea and buckbrush.
39.54	Point for the N $\frac{1}{4}$ sec. cor. of sec. 5, T. 25 N., R. 19 E., is on the Fifth Standard Parallel North and at midpoint bet. the closing cors.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a collar of stone to cap, 3 ft. base, with aluminum cap mkd.
	T26N R19E
	1 S 5 T25N R19E
	1981
39.75	The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a volcanic stone, $18x9x7$ ins., firmly set in a mound of stone, dimly mkd. $\frac{1}{4}$ on the N. face.
	At the corner point
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone to cap, 3 ft. base, with aluminum cap mkd.
	S C T26N R19E 4 S 32
	1981
	Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.
	S. 89° 54' W., beginning new measurement.
	Over mountainous land.
7.00	Spur, slopes NNW.
21.80	Spur, slopes N.
39.52	The closing cor. of secs. 5 and 6, T. 25 N., R. 19 E., monumented with a trapstone, 21x6x6 ins., firmly set in a mound of stone, plainly mkd. with 5 grooves on the E. face and 1 groove on the W. face and CC on the S. face.
	At the corner point