

323

DEPENDENT RESURVEY OF
THE FIFTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 19 EAST, MDM, NEVADA

CHAINS	
40.13	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.</p> <p style="text-align: center;">T26N R19E S 32 <u>S 6 S 5</u> T25N R19E C C</p> <p style="text-align: center;">1981</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>The standard cor. of secs. 31 and 32, monumented with a volcanic stone, 19x13x10 ins., firmly set in a mound of stone, plainly mkd. with 5 grooves on the E. face, 1 groove on the W. face and dimly mkd. SC on the N. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock and in a mound of stone to cap, 6 ft. base, with aluminum cap mkd.</p> <p style="text-align: center;">S C T26N R19E <u>S 31 S 32</u></p> <p style="text-align: center;">1981</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <hr/> <p>S. 89° 56' W., along the S. bdy. of sec. 31.</p> <p>Over mountainous land, covered with medium sagebrush and native grass.</p>
39.41	<p>Point for the N ¼ sec. cor. of sec. 6, T. 25 N., R. 19 E., is on the Fifth Standard Parallel North and at proportionate distance.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.</p> <p style="text-align: center;">T26N R19E <u>¼ S 6</u> T25N R19E</p> <p style="text-align: center;">1981</p>