

345

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 26 N., R. 19 E., MDM, NEVADA

CHAINS 81.46	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 88° 25' W., bet. secs. 18 and 19.</p> <p>Over nearly level land, across dry lake bed with no vegetation.</p>
40.66	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R19E S 18 $\frac{1}{4}$ ————— S 19</p> </div> <p style="text-align: center;">1981</p> <p>Set a steel fence post, 5$\frac{1}{2}$ ft. long, alongside the aluminum post.</p>
81.01	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a basalt stone, 12x10x3 ins., firmly set in a mound of earth, no marks visible. This point correlates well with other existing original cors. and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R18E R19E S 13 S 18 S 24 S 19</p> </div> <p style="text-align: center;">1981</p> <p>Deposit the original cornerstone alongside the aluminum post.</p> <hr/>