

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 28 N., R. 56 E., MDM, NEVADA

CHAINS

N. 5° 19' W., beginning new measurement.

Over rolling land.

40.26 The cor. of Tps. 28 and 29 N., Rs. 55 and 56 E., monumented with an iron post, 3 ins. diam., firmly set, showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 28 N., R. 55 E., executed under Group No. 195. Rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor. and set a steel fence post, 5 ft. long, alongside the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 28 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
A. J. Hatch, U. S. Deputy Surveyor,  
in 1872,  
and a Portion Resurveyed by Philip L. Inch,  
Cadastral Engineer, in 1939,  
and a Portion Resurveyed by Emil Voigt,  
Associate Cadastral Engineer, and James W. Hardison,  
Assistant Cadastral Engineer,  
in 1944.

From the cor. of Tps. 28 and 29 N., Rs. 56 and 57 E., identical with Cor. No. 1 of H.E.S. 230, monumented with an iron post, 3 ins. diam., firmly set, showing 20 ins. above the ground and in a mound of stone to cap, 4 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 28 N., R. 57 E., executed under Group No. 191. Remark the brass cap to read as follows:

T29N  
R56E R57E  
S 36 | S 31  
S 1 | S 6  
T28N  
1981  
1944

WEST, bet. secs. 1 and 36.

Over mountainous land, through scattered sagebrush and willows.

20.00 Improved gravel road, bears WNW. and ESE.

20.80 Fence, bears WNW. and ESE., enter cultivated land.

29.40 Toyn Creek, 10 lks. wide, 6 ins. deep, course WNW.

39.78 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, identical with Cor. No. 8 of H.E.S. No. 230, monumented with an iron post, 1 in. diam., firmly set, showing 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 28 N., R. 56 E., executed under Group No. 191. Remark the brass cap to read as follows: