

SURVEY OF THE WEST BOUNDARY,
T. 28 N., R. 57 E., MDM, NEVADA

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with aluminum cap mkd.</p> <p style="text-align: center;">T28N R56E R57E 1¼ S 18</p> <p style="text-align: center;">1981</p> <p>From this corner, Cor. No. 2 of H.E.S. No. 193, monumented with a quartz stone, 8x6x6 ins., firmly set in a mound of stone, plainly mkd. 2 HES 193 on the NE. face, bears S. 16° 16' E., 4.90 chs. dist.</p> <p style="text-align: center;">At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.</p> <p style="text-align: center;">T28N COR 2 R57E HES S 18 193</p> <p style="text-align: center;">1981</p> <p style="text-align: center;">Bury the cornerstone alongside the aluminum post.</p>
40.79	The E. ¼ sec. cor. of sec. 13, T. 28 N., R. 56 E., hereinafter described.
51.60	Trail road, bears E. and W.
80.00	<p>Point for the cor. of secs. 7 and 18.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T28N T28N R57E S 13 S 7 S 18 R56E</p> <p style="text-align: center;">1981</p> <p>Set a steel fence post, 5 ft. long, alongside the aluminum post.</p> <p>Land, rolling. Soil, loam. Timber, juniper and pinion; undergrowth, sagebrush.</p>
	NORTH, along the W. bdy. of sec. 7.
	Over mountainous land.
0.39	The closing cor. of secs. 12 and 13, T. 28 N., R. 56 E., hereinafter described.
40.00	Point for the W. ¼ sec. cor. of sec. 7.