

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 28 N., R. 56 E., MDM, NEVADA

CHAINS 27.94	<p>Intersect the W. bdy. of sec. 19, T. 28 N., R. 57 E.</p> <p>Point for the closing cor. of secs. 24 and 25, NORTH 0.1 lks. from the tangent.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T28N R56E T28N CC $\frac{S}{S}$ $\frac{24}{25}$ S 19 R57E</p> </div> <p style="text-align: center;">1981</p> <p>From this corner, the cor. of secs. 19 and 30, T. 28 N., R. 57 E., hereinbefore described, bears SOUTH, 1.83 chs. dist.</p> <p>Land, mountainous. Soil, loam and gravelly. Timber, none; undergrowth, sagebrush.</p> <hr/> <p>Point for the E. ¼ sec. cor. of sec. 25, is at midpoint bet. the closing cors. and on the W. bdy. of sec. 30, T. 28 N., R. 57 E.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T28N R56E R57E ¼ S 25 </p> </div> <p style="text-align: center;">1981</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, the W. ¼ sec. cor. of sec. 30, T. 28 N., R. 57 E., hereinbefore described, bears SOUTH, 2.15 chs. dist.</p> <hr/> <p>From the ¼ sec. cor. of secs. 13 and 24.</p> <p>EAST, bet. secs. 13 and 24, on a transit line describing the tangent.</p> <p>Over rolling land.</p>
36.10	<p>Intersect the W. bdy. of sec. 18, T. 28 N., R. 57 E.</p> <p>Point for the closing cor. of secs. 13 and 24, NORTH 0.1 lks. from the tangent.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with aluminum cap mkd.</p>