

412

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 28 N., R. 56 E., MDM, NEVADA

CHAINS

T28N  
R56E | T28N  
CC  $\frac{S\ 13}{S\ 24}$  | S 18  
| R57E

1981

From this corner, the cor. of secs. 18 and 19, T. 28 N., R. 57 E., hereinbefore described, bears SOUTH, 1.19 chs. dist.

Land, rolling.  
Soil, loam and gravelly.  
Timber, none; undergrowth, sagebrush.

---

Point for the E.  $\frac{1}{4}$  sec. cor. of sec. 24, is at midpoint bet. the closing cors. and on the W. bdy. of sec. 19, T. 28 N., R. 57 E.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with aluminum cap mkd.

T28N  
R56E R57E  
 $\frac{1}{4}$  |  
S 24 |

1981

From this corner, the W.  $\frac{1}{4}$  sec. cor. of sec. 19, T. 28 N., R. 57 E., hereinbefore described, bears SOUTH, 1.51 chs. dist.

---

From the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13.

EAST, bet. secs. 12 and 13, on a transit line describing the tangent.

Over rolling land.

- 6.70 Trail road, bears NNW. and SSE.
  - 9.00 Corral Creek, 10 lks. wide, 6 ins. deep, course NNW.
  - 10.00 Fence, bears NNW. and SSE.
  - 39.01 Intersect the W. bdy. of sec. 7, T. 28 N., R. 57 E.
- Point for the closing cor. of secs. 12 and 13, NORTH 0.2 lks. from the tangent.
- Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T28N  
R56E | T28N  
CC  $\frac{S\ 12}{S\ 13}$  | S 7  
| R57E

1981