

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 28 N., R. 56 E., MDM, NEVADA

CHAINS

Set a steel fence post, 5 ft. long, alongside the aluminum post.

From this corner, the cor. of secs. 7 and 18, T. 28 N., R. 57 E., hereinbefore described, bears SOUTH, 0.39 chs. dist.

Land, rolling.  
Soil, loam and gravelly.  
Timber, none; undergrowth, sagebrush.

Point for the E.  $\frac{1}{4}$  sec. cor. of sec. 13, is at midpoint bet. the closing cors. and on the W. bdy. of sec. 18, T. 28 N., R. 57 E.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam. 12 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with aluminum cap mkd.

T28N  
R56E R57E  
 $\frac{1}{4}$ |  
S 13|

1981

From this corner, the W.  $\frac{1}{4}$  sec. cor. of sec. 18, T. 28 N., R. 57 E., hereinbefore described, bears SOUTH, 0.79 chs. dist.

From the  $\frac{1}{4}$  sec. cor. of secs. 1 and 12.

EAST, bet. secs. 1 and 12, on a transit line describing the tangent.

Over rolling land.

40.83 Intersect the W. bdy. of sec. 6, T. 28 N., R. 57 E.

Point for the closing cor. of secs. 1 and 12, NORTH 0.2 lks. from the tangent.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T28N  
R56E | T28N  
CC  $\frac{S}{S}$   $\frac{1}{12}$  | S 6  
| R57E

1981

Set a steel fence post, 5 ft. long, alongside the aluminum post.

From this corner, the cor. of secs. 6 and 7, T. 28 N., R. 57 E., hereinbefore described, bears SOUTH, 0.29 chs. dist.

Land, rolling.