

DEPENDENT RESURVEY OF THE
FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 54 E., MDM, NEVADA

CHAINS

- 0.71 The closing cor. of secs. 5 and 6, T. 20 N., R. 54 E., hereinafter described.
- 40.38 The standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a volcanic stone, 10x6x4 ins., plainly mkd. $\frac{1}{4}$ SC on the N. face, firmly set in a mound of earth.
- At the corner point
- Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- SC
T21N R54E
 $\frac{1}{4}$ S 31
1981
- Deposit the original cornerstone alongside the aluminum post, 3 ft. base, 2 ft. high, N. of cor.
-
- N. 89° 51' W., beginning new measurement.
- Over nearly level land.
- 0.75 The N. $\frac{1}{4}$ sec. cor. of sec. 6, T. 20 N., R. 54 E., hereinafter described.
- 40.46 The standard cor. of Tps. 20 and 21 N., Rs. 53 and 54 E., monumented with a wooden post, 5x8 ins., firmly set and exposed $4\frac{1}{2}$ ft. above ground with a metal tag on top of the wooden post stamped "Township Corner". This post was set on May 18, 1976 by Jerry L. Machacek and is accepted as a careful and faithful perpetuation of the position of the original corner. There is no remaining evidence of the iron post as described in the field notes of the dependent resurvey of the E. bdy. of T. 20 N., R. 53 E., executed under Group No. 133.
- This post is part of a fence which bears N. and S.
- From this corner
- An aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 1° 50' E., 37.0 ft. dist., with aluminum cap mkd. T21N R54E S31 RM 37.0 ft. 1981, and an arrow pointing to the true corner.
- An aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground for a reference monument bears N. 83° 38' E., 42.8 ft. dist., with aluminum cap mkd. "XRM 42.8 ft. 1981" and an arrow pointing to the true corner.
- A marked stone bears S. 0.045 chs. dist.