

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 24 N., R. 37 E., MDM, NEVADA

CHAINS
79.87

The original cor. of Tps. 23 and 24 N., Rs. 36 and 37 E., monumented with the decayed remains of a squared wooden post, 24 ins. long, $2\frac{1}{2}$ ins. diam., loosely set 4 ins. in the ground, with illegible scribe marks visible.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T24N
R36E R37E
S 36 | S 31
S 1 | S 6
T23N

1981

Reset the wooden post and set a steel fence post, 5 ft. long, alongside the aluminum post.

From this corner, U.S.G.S. triangulation station "SALT," monumented with a standard aluminum tablet stamped SALT 1965, set in top of a concrete monument projecting 4 ins. above the ground, bears S. $7^{\circ} 10'$ E., 160.32 chs. dist.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 24 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
T. K. Stewart and G. W. Conkling,
U. S. Deputy Surveyors,
in 1881.

From the cor. of Tps. 23 and 24 N., Rs. 37 and 38 E.
N. $0^{\circ} 05'$ E., bet. secs. 31 and 36.

Over rolling land, through scattered greasewood.

39.50 Trail road, bears NW. and SE.

40.25 The original $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a limestone, 12x4x4 ins., plainly mkd. $\frac{1}{4}$ on the W. face, firmly set 6 ins. in the ground. (Record wooden post.)

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.