

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 24 N., R. 37 E., MDM, NEVADA

| CHAINS | |
|--------|--|
| | <p>T24N R36E R37E $\frac{1}{4}$ S 12 S 7</p> <p>1981</p> <p>Bury the cornerstone and set a steel fence post, 5 ft. long, alongside the aluminum post.</p> <hr/> <p>N. 0° 48' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>23.80 Bladed road, bears E. and W.</p> <p>40.50 Trail road, bears E. and W.</p> <p>40.64 The original cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 16x6x6 ins., plainly mkd. with 5 grooves on the S. face and 1 groove on the N. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.</p> <p>T24N R36E R37E S 1 S 6 <hr/>S 12 S 7</p> <p>1981</p> <p>Bury the cornerstone and set a steel fence post, 5 ft. long, alongside the aluminum post.</p> <hr/> <p>N. 0° 34' E., bet. secs. 1 and 6.</p> <p>Over rolling land, through scattered greasewood.</p> <p>40.40 The original $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a granite stone, 12x10x8 ins. plainly mkd. $\frac{1}{4}$ on the W. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.</p> |